

iS-15M

Mini, Fanless Digital Signage PC



Features

- Rugged Fanless Design
- Suitable for Medium Level Digital Signage Applications
- Supports Dual Display via DVI & VGA, Ports
- <20W Power Consumption
- Supports Landscape & Portrait Video Modes

Fanless

4x USB

<20W

2x COM

Dual Display

2x LAN

VGA + DVI

Specifications

CPU	Atom
Memory	Up to 1GB
Video	VGA, DVI-D
Video Mode	Landscape, Portrait
LAN	10/100, GbE
USB 2.0	4x Ports
COM	2x RS232 (1x RS485)
Hard Disk	SATA 2
Solid State Disk	Optional
Compact Flash	Yes

Watchdog Timer	256 Levels
Hardware Monitor	Yes
Fanless	Yes
Audio	ALC 662
Expansion	
Dimensions (mm)	171W x 50H x 113D
Power Supply	12VDC
Power Consumption	<20W
Operating Temp	0°C - 60°C
Warranty	2 Years

Configuration Options

CPU	Memory	Storage *	Operating System **
1.6GHz	512MB		No O/S
	1GB		Win XP ProE
			Win XP Embedded
			Win Vista

* Storage options include Compact Flash Modules, Rotating or Solid State Hard Disk Drives (IDE Disk On Module or SATA SSD), or a combination of these. Call for more details.

** Players are available with no operating system or standard Windows install. We offer a customised XP Embedded build incorporating end-user application software. Call for details.